

Truespoke 3-Bar Spinner and Donut Cap Installation Instructions

The Tower shown below has been threaded into your spinner or Donut cap for testing.

***PLEASE UN-SCREW THE TOWER FROM THE BACK OF THE SPINNER OR "DONUT" CAP FIRST.**

You may then follow the below instructions to complete your installation. Thank you.



Your caps come with the set screws already installed. You will also receive an Allen wrench and extra screws.



AFTER your wheel and tire have been mounted and balanced, place the tower into the center of the wheel hub as shown. Make sure the tower is fully inserted and seated.



Above: Once the tower is in place, using the provided Allen wrench, tighten each set screw equally until they are tight and the tower cannot be moved. **Make certain that the tower is inserted as far as it will go before tightening the screws.**



The 3-Bar Spinner has three set screws, one under each blade. Tighten the set screw part way before installing it onto the tower.



The Donut Cap has one set screw. Tighten the screw partially before installing it onto the tower.



Above and below: Twist-on your Spinner or Donut cap until it is tight. Once the cap is tight, tighten each set screw until the screws are tight. Do not over-tighten the screws or they may strip. Make sure you cannot move the cap by hand. Once you have verified your cap is tight, you are finished. Enjoy!



- It is **very important** that you do not install the tower prior to balancing the wheels and tires. Only install the tower **AFTER** you have balanced the wheels and tires or you will not be able to obtain a proper balancing

Special note on the 3-Blade Spinner: Do not tighten your set screws all the way until after your lug nuts have been installed. You must be able to rotate the spinner to be able to tighten your lug nuts. Once your lug nuts have been tightened, you may finish tightening down your three set screws. Make sure your spinner cap is tight and cannot be moved. Please email or call us with any questions or comments.
Thank you.